



WP 15X



WP20X



WP30X



WP40X



WP20H



WP20I



WP30H



WP30I



Model	WP15X	WP20X	WP30X	WP40X
Engine	BS100	BS220X	BS220C	BS270
Starting system	Recoil Starter			
Bore × Stroke	52 × 46mm	70 × 54mm	70 × 54mm	77 × 58mm
Displacement	97cc	212cc	212cc	270cc
Compression Ratio	5.6:1	8.5:1	8.5:1	8.2: 1
Pump set	Self-priming pump	Self-priming pump	Self-priming pump	Self-priming pump
Suction port diameter	40mm	50mm	80mm	100mm
Discharge port diameter	40mm	50mm	80mm	100mm
Suction head lift	6m	9m	7m	9m
total head lift	15m	35m	30m	35m
Discharge capacity	10 (m³/h)	25 (m³/h)	35 (m³/h)	60 (m³/h)
Dimensions(L×W×H)	365 × 320 × 380mm	540 × 430 × 445mm	540 × 430 × 445mm	630 × 470 × 580mm
N.G/W.G	11/12kgs	24/26kgs	26/28kgs	46/48kgs
Quantity(20GP/40HQ)	696/1645	280/690	280/690	168/348



Model	WP20H	WP30H	WP20I	WP30I
Engine	BS220	BS420	BS220	BS220
Starting system	Recoil Starter			
Bore × Stroke	70 × 54mm	90 × 66mm	70 × 54mm	70 × 54mm
Displacement	212cc	420cc	212cc	212cc
Compression Ratio	8.5:1	8.0:1	8.5:1	8.5:1
Pump set	High-pressure pump	High-pressure pump	Cast iron pump	Cast iron pump
Suction port diameter	50mm	80mm	50mm	80mm
Discharge port diameter	50mm,40mm,40mm	80mm,40mm,40mm	40mm	80mm
Suction head lift	11m	19m	11m	9
total head lift	65m	95m	40m	35
Discharge capacity	35 (m³/h)	85 (m³/h)	30 (m³/h)	40 (m³/h)
Dimensions(L×W×H)	535 × 430 × 480mm	665 × 505 × 580mm	535 × 430 × 480mm	535 × 430 × 480mm
N.G/W.G	25/27kgs	48/50kgs	24/26kgs	26/28kgs
Quantity(20GP/40HQ)	224/575	156/324	224/575	224/575